Remanufactured Straddle Carriers















	M200H	M300H	M400H	M400A	M500A	M600A	M700A
Standard Engine*	Cummins 4BT3.9-C Turbo Diesel	Cummins 6BT5.9-C Turbo Diesel	Cummins 6BT5.9-C Turbo Diesel	Cummins 6BT5.9-C Turbo Diesel	Cummins 6CT8.3-C Turbo Diesel	Cummins 6CT8.3-C Turbo Diesel	Cummins 6CT8.3-C Turbo Diesel
Standard Transmission*	Allison AT545 Automatic	Allison AT545 Automatic	Allison AT545 Automatic	Allison MT643 Automatic	Allison MT643 Automatic	Allison MT643 Automatic	Allison MT643 Automatic
Frame Construction †	H-Frame	H-Frame	H-Frame	A-Frame	A-Frame	A-Frame	A-Frame
Lifting Capacity	20,000 lbs.	30,000 lbs.	40,000 lbs.	40,000 lbs.	50,000 lbs.	60,000 lbs.	70,000 lbs.
Steering	Full Power, Double- Acting Cylinder						
Brakes	Air over Hydraulic, Dual Path						
Suspension	Four Wheel, Independent						
Standard Tires	9.00 x 20	11.00 x 20	12.00 x 20	14.00 x 20	14.00 x 24	14.00 x 24	16.00 x 25
Fuel Capacity	20 gal.	20 gal.	20 gal.	60 gal.	60 gal.	60 gal.	60 gal.
Hydraulic Capacity	28 gal.	28 gal.	28 gal.	60 gal.	60 gal.	60 gal.	60 gal.
Package Width Range ‡**	46" to 100"	52" to 100"	52" to 100"	58" to 88"	58" to 88"	58" to 88"	58" to 88"
Overall Width Range ‡**	84.6" to 138.6"	91" to 139"	98" to 146"	114" to 144"	117.5" to 147.5"	117.5" to 147.5"	117.5" to 147.5"
Package Height Range ‡**	48" to 78"	54" to 84"	54" to 84"	60" to 90"	60" to 90"	60" to 90"	60" to 90"
Overall Height Range ‡**	128" to 158"	132.8" to 162.8"	136.2" to 166.2"	148.5" to 176.5"	144" to 172"	144" to 172"	144" to 172"
Overall Length ‡	176"	191"	212"	231"	238"	238"	238"
Approximate Machine Weight ‡	12,500 lbs.	13,300 lbs.	15,500 lbs.	36,000 lbs.	36,000 lbs.	36,000 lbs.	36,000 lbs.

^{*} Options Available

^{**} Custom frame sizes are available. Click Here.

[†] See frame style difference explanation. (insert link to frameinfo.htm)

[‡] See brochures for more information. M200H-M400H, M400A-M700A.